



780Gloss

Product Information

	 Bristol 780 Gloss is a pure acrylic, water based, high quality coating This coating can be used as a pre-treating agent and sealer for interior use as well as an effective exterior protective weather proof coating for paintwork. Bristol 780 Gloss also provides an alternative solution for sealing fireproofed plywood panels, as it seals substrate and prevents salts from leeching through the painted surfaces and damaging finished work.
Drying Time	1-2 Hours achieves maximum durability if left overnight
Re-Coat	When touch dry
Coverage	10m2 per Litre. Actual coverage depends on many factors, such as the shape of the object, the porosity of the surface, the method of application and the circumstances in which it is applied.
Adhesion	Excellent on most surfaces
Available Sizes	1 Litre, 2.5 Litres, 5 Litres and 10 Litres
Application	Paint brush, roller or conventional spray system
Warning	Do not apply in cold conditions or high humidity
Disclaimer If you are no	t a professional or experienced decorator, we would advise you to

take professional advice when painting, as we are not able to advise on the various surfaces and conditions you may encounter.

> We do not recommend to use Bristol paint on surfaces where water will gather or high traffic areas such as doors. Use a water-based acrylic undercoat or primer if possible, and allow to dry completely. If you are using another manufacturer's product e.g. undercoat or primer, with any Bristol product, we recommend you test a small section first, to ensure compatibility.