

AquaFast

Product Information

Group	Non-toxic water based lacquer
Description	AquaFast is an exceptionally fast curing, specialist coating, which can be thinned off with water and used for furniture as well as floors etc.
Properties	Exceptionally fast curing Very low odour Easy maintenance and superior durability Ideal for sealing and lacquering woodblock and parquet type flooring AquaFast is intermixable with Bristol paint. It can bond colours onto products giving an exceptionally hardwearing glaze finish Bonds to substrates such as PVC, vinyl and vacuum formed materials
Application	AquaFast is especially suitable for floors, furniture, staircases etc. In order to obtain wear-resistant result.

Technical Data

Colour	Colourless
Finish	Satin
Density	Approximately 1.05 gr/cm ³
Flash point	N/A
Coverage	10m ² per Litre. Actual coverage depends on many factors, such as the shape of the object, the porosity of the surface, the method of application and the circumstances in which it is applied.
Application Conditions	Substrate and surrounding temperature should be between 10°C and 30°C during application and drying. Relative humidity no more than 75%.
Drying Times	At 20°C and 50% R.H. Dust Dry: 30 Minutes Adhesion Free: 1 Hour Overcoat: Within 2 Hours Thoroughly Dry: 16 Hours
Instructions For Use	Stir well before use. New floors etc. should be sanded prior to first application. Additional coats must be applied within 2 hours. If the floor is left longer than this length of time, it may be necessary to re sand the surface. Additional coats should be applied dependant on the level of protection required.

Technical Data Cont.

Applying	Airless spray	Air spray	Brush/roller
Thinning	Water	Water	Water
Amount	5-10%	10 - 15%	0 - 5%
Nozzle Size	0.018 - 0.021	1.5 - 2.0mm	
Spray Pressure	80 - 120 Bar	3 - 4 Bar	
Cleaning Tools	Clean equipment and brushes with water.		
Packaging Size	2.5, 5 Litres		
Shelf Life	At least 1 year if stored in a dry and cool place in unopened original packaging between 5° - 35°C. AquaFast is sensitive to frost and must be protected from frost in storage.		

Safety

Safety Aspects	The user must comply with the prevailing legislation and regulations with aspect to disposal of wastes, health and safety. For further information, see the relevant safety data sheet.
----------------	--

Disclaimer If you are not a professional or experienced decorator, we would advise you to take professional advice when painting, as we are not able to advise on the various surfaces and conditions you may encounter.

We do not recommend to use Bristol paint on surfaces where water will gather or high traffic areas such as doors. Use a water-based acrylic undercoat or primer if possible, and allow to dry completely. If you are using another manufacturer's product e.g. undercoat or primer, with any Bristol product, we recommend you test a small section first, to ensure compatibility.