

AquaPlus

Product Information

Group	Water based air drying paint
Description	Non-toxic PVA based, water bound coating
Properties	Can be intermixed with Bristol Paints Works as an extender and conditioner Greatly increases surface flexibility Especially useful when spraying Does not stick in transport or in storage
Application	AquaPlus can be intermixed in conjunction with Bristol Paint. Especially useful when spraying

Technical Data

Colours	Clear
Finish	Semi-Gloss
Density	Approximately 1.07KG/1
Coverage	10m ² per Litre. Actual coverage depends on many factors, such as the shape of the object, the porosity of the surface, the method of application and the circumstances in which it is applied.
Application Conditions	Substrate and surrounding temperature should be between 5°C and 30°C during application and drying. Relative humidity no more than 85%
Drying Times	At 20°C and 65% relative humidity Dust dry 2 Hours Adhesion free 4 Hours Thoroughly dried 24 Hours
Instructions For Use	To use in conjunction with Bristol Paints, firstly a base colour should be applied. For the final coat intermix 25% of AquaPlus to the colour for a more durable finish. To use AquaPlus as a top dressing stir well before use. Dilute with a ratio of 1:1 or up to 1:2 depending on the porosity of the substrate and the amount of sheen required. Can be used as an extender with Bristol Metallics Do not use with any other Bristol Aqua Coatings or Lacquers

BRISTOL



Applying	Airless spray	Air spray	Brush/roller
Thinning	Water	Water	Water
Amount	5 - 10%	10 - 15%	0 - 5%
Nozzle Size	0.018 - 0.021	1.5 - 2.0mm	
Spray pressure	85 - 120 Bar	3 - 4 Bar	
Cleaning Tools	Clean equipment and brushes with water		
Packaging size	1Litre, 2.5Litre, 5Litre, 10Litre		
Shelf Life	At least 1 year if stored in a dry and cool place in unopened original packaging		

Safety

Safety Aspects	The user must comply with the prevailing legislation and regulations with respect to disposal of wastes, health and safety For further information, see the label and the relevant safety information sheet.
----------------	---

Disclaimer If you are not a professional or experienced decorator, we would advise you to take professional advice when painting, as we are not able to advise on the various surfaces and conditions you may encounter.

We do not recommend to use Bristol paint on surfaces where water will gather or high traffic areas such as doors. Use a water-based acrylic undercoat or primer if possible, and allow to dry completely. If you are using another manufacturer's product e.g. undercoat or primer, with any Bristol product, we recommend you test a small section first, to ensure compatibility.