

Bristol Glitter

Product Information

Group	Water based air drying paint
Description	Bristol Glitter is an air drying water-based paint formulated for interiors. It comprises coloured polyester particles held in a PVA solution, which dries clear.
Properties	Can be applied to a wide range of substrates. Can be diluted with water between 5 - 10% All Bristol Scenic Paints can be over sprayed with Bristol Glitter Density of coloured particles can be built up from a light mist coating to a solid finish
Application	Bristol Glitter is ready for use, can be thinned with water and is preferably used indoors. The substrate must have a good structure for adhesion and must be dry, clean, dust free and grease free.

Technical Data

Colours	18 colours
Finish	Glitter
Density	From 1.25 - 1.52 gr/cm ³ (dependant on colour)
Output	Theoretically coverage is about 4-6m ² /Litre The actual coverage depends on many factors such as the shape of the object, the porosity of the surface, the method of application and the circumstances in which it is applied. Due to the nature of this product, actual surface coverage is dependent on the density of the application.
Application Conditions	Substrate and surrounding temperature should be between 7°C and 30°C during application and drying. Relative humidity no more than 75%
Drying Time	At 20°C and 65% relative humidity no more than 75% Dust dry 30 minutes Tack free 1 hour Overcoat 5 hours Thoroughly dry 24 hours
Instructions For Use	Stir well before use. It may be thinned with 5 - 15% water. Bristol Glitter is best applied with a paint spray. HVLP spray is recommended. Work in one direction keeping the sprayer in constant motion. Application by roller (mohair) is possible, but the result is less fine and care must be taken not to 'over work' the paint when applying. Glitter Paint can be glazed with a protective coating of AquaLak or 780 Coating.

Instructions For Use Cont.

Applying	Airless spray	Air spray	Brush/roller
Thinning	Water	Water	Water
Amount	5 - 10%	10 - 15%	0 - 5%
Nozzle Size	0.018 - 0.021	1.5 - 2.0mm	
Spray pressure	85 - 120 Bar	3 - 4 Bar	

Coverage In practice the coverage is approximately 6m²/Litre
The coverage is very much dependant of the application method, quality of the substrate and the form of the object.

Cleaning Tools Clean equipment and rollers with water

Packaging Size 0.125, 0.5, 2.5KG

Shelf Life At least 1 year if stored in a dry and cool place in unopened original packaging.

Safety

Safety Aspects The user must comply with the prevailing legislation and regulations with respect to disposal of wastes and health and safety.

Disclaimer If you are not a professional or experienced decorator, we would advise you to take professional advice when painting, as we are not able to advise on the various surfaces and conditions you may encounter.

We do not recommend to use Bristol paint on surfaces where water will gather or high traffic areas such as doors. Use a water-based acrylic undercoat or primer if possible, and allow to dry completely. If you are using another manufacturer's product e.g. undercoat or primer, with any Bristol product, we recommend you test a small section first, to ensure compatibility.