

# ExpoMulti

## Product Information

Group	Water soluble high adhesion paint
Description	Water-based high adhesion paint with excellent properties for interior use. Based on an acrylic emulsion
Application	<b>ExpoMulti</b> is a specially developed latex bound paint and is used, where a high adhesion quality finish is required. Because of its hardwearing characteristics, <b>ExpoMulti</b> is a particularly suitable for use as a primer for fibreglass and previously epoxy coated surfaces. When long-term durability is needed, we advise applying several layers of <b>AquaLak</b> as protective topcoat. Application can be made by brush, roller or spray.

## Technical Data

Colour	White, Black or Colour
Finish	Silky Matt
Density	Approximately 1.44kg/dm <sup>3</sup>
Solids Content	61% (m/m) 26% (v/v)
Coverage	10m <sup>2</sup> per Litre. Actual coverage depends on many factors, such as the shape of the object, the porosity of the surface, the method of application and the circumstances in which it is applied.
Application Conditions	Substrate and surrounding temperature should be between 5°C and 30°C during application and drying. Relative humidity no more than 85%
Drying Times	At 20°C and 65% R.H. and a wet coating thickness of 100-150µm: Dust dry                      30 minutes Tack free                      1 hour Overcoat                      5 hours Thoroughly dry              24 hours
Instructions For Use	Stir well before use and, if desired thin with water. The substrate must be dry, clean and grease free. Untreated non-porous surfaces i.e. cement, cast concrete and should be given two coats of <b>ExpoMulti</b> leaving at least 5 hours to dry between coats. Untreated porous surfaces i.e. plaster, float finish, lime plaster should be primed with a suitable stabilizing solution, preferably water based. After drying for at least 24 hours, give two coats of <b>ExpoMulti</b> , leaving at 5 hours to dry between coats.

## Instructions For Use Cont.

Applying	Airless spray	Air spray	Brush/roller
Thinning	Water	Water	Water
Amount	5 - 10%	10 - 15%	0 - 5%
Nozzle Size	0.018 - 0.021	1.5 - 2.0mm	
Spray pressure	80 - 120 Bar	3 - 4 Bar	
Cleaning Tools	Clean equipment and brushes with water		
Packaging Size	2.5, 5, 10 Litre		
Shelf Life	At least 1 year if stored in a dry and cool place in unopened original packaging. <b>ExpoMulti</b> is sensitive to frost. Protect from frost in storage.		

## Safety

Safety Aspects	The user must comply with the prevailing legislation and regulations with respect to disposal of wastes, health and safety. For further information, see the label and the relevant safety information sheet.
----------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Disclaimer** If you are not a professional or experienced decorator, we would advise you to take professional advice when painting, as we are not able to advise on the various surfaces and conditions you may encounter.

We do not recommend to use Bristol paint on surfaces where water will gather or high traffic areas such as doors. Use a water-based acrylic undercoat or primer if possible, and allow to dry completely. If you are using another manufacturer's product e.g. undercoat or primer, with any Bristol product, we recommend you test a small section first, to ensure compatibility.